
12X10X4 PREMIUM LINE















Atex pending, contact factory for details

PREMIUM POLYCARBONATE ENCLOSURE

Features and Benefits

- 16 Standard configurations including hinged or non-hinged lids in 2-screw, 4-screw, or stainless steel metal latched lids.
- Standard color light gray with a gloss finish.
- Best material bases, opaque covers and clear covers are all made of high-impact, UV resistant polycarbonate.
- Easy ordering one part number includes base, lid, mounting feet or flanges and all lid fastening hardware (mounting panels sold separately).
- Flexible interior mounting features the unique and patented Integra adjustable depth "T-Rail" back panel mounting system (back panel and adjustable brackets sold separately).
- Features multiple bosses for easy installation of devices and DIN rails.
- UL-50 / c-UL Listed (files # E229365, # E207562)

Our Premium Line enclosures are the most durable, aesthetically pleasing, non-metallic Nema UL rated enclosures available. From the extremely versatile mounting options inside the enclosure to having the most off-the-shelf accessories, the Integra "Made In the USA" Premium Line enclosures provide great value to any application.

Mechanical and Thermal	Test Spec.	Unit	Premium Line	
Instrumented Dart Impact @ 73° F		in/lb.	565	
Falling Ball Impact @ 73° F	UL-746	in/lb.	900	
Deflection Temperature @ 264 psi	ASTM D648	Deg. F	270	
Modulus of Elasticity	ASTM D790	ksi	340	
Temperature Range		Deg. F	-40 to 265	
Flammable / UV Ratings	Test Spec.	Unit	Premium Line	
Flame Rating - UL	UL 94	-	5VA	
Outdoor UV Exposure	UL	-	F1	

12104 P/N	4X IP66	6P IP68	Hinged Cover	Screw Cover	Opaque Cover	Clear Cover	Mounting Feet	Mounting Flange	Stainless Steel Locking Latch	T-Rail System
H12104S	✓	✓		✓	✓		✓			✓
H12104SC	✓	✓		✓		✓	✓			✓
H12104SF	✓	✓		✓	✓			✓		✓
H12104SCF	✓	✓		✓		✓		✓		✓
H12104H	✓		✓	✓	✓		✓			✓
H12104HC	✓		✓	✓		✓	✓			✓
H12104HF	✓		✓	✓	✓			✓		✓
H12104HCF	✓		✓	✓		✓		✓		✓
H12104HLL	✓		✓		✓		✓		✓	✓
H12104HCLL	✓		✓			✓	✓		✓	✓
H12104HFLL	✓		✓		✓			✓	✓	✓
H12104HCFLL	✓		✓			✓		✓	✓	✓
H12104H-6P	✓	✓	✓	✓	✓		✓			✓
H12104HC-6P	✓	✓	✓	✓		✓	✓			✓
H12104HF-6P	✓	✓	✓	✓	✓			✓		✓
H12104HCF-6P	✓	✓	✓	✓		✓		✓		✓

TORQUE SPECIFICATIONS - Mounting Brackets - 1/4"-20 x 0.25 SS, countersunk phillips drive screws (torque limit = 20 in. lbs.) | Covers / Doors - Torque for corner screws is 10 in. lbs.



12X10X4 PREMIUM LINE

