18X16X10 PREMIUM LINE





* This size also available in low profile hinge. Call Integra for more details.



Atex pending, contact factory for details

PREMIUM POLYCARBONATE ENCLOSURE

Features and Benefits

- 16 Standard configurations including hinged or non-hinged lids in 2-screw, 4-screw, or stainless steel metal latched lids.
- Standard color light gray with a gloss finish.
- Best material bases, opaque covers and clear covers are all made of high-impact, UV resistant polycarbonate.
- Easy ordering one part number includes base, lid, mounting feet or flanges and all lid fastening hardware (mounting panels sold separately).
- Flexible interior mounting features the unique and patented Integra adjustable depth "T-Rail" back panel mounting system (back panel and adjustable brackets sold separately).
- Features multiple bosses for easy installation of devices and DIN rails.
- UL-50 / c-UL Listed (files # E229365, # E207562)

Our Premium Line enclosures are the most durable, aesthetically pleasing, non-metallic Nema UL rated enclosures available. From the extremely versatile mounting options inside the enclosure to having the most off-the-shelf accessories, the Integra "Made In the USA" Premium Line enclosures provide great value to any application.

Mechanical and Thermal	Test Spec.	Unit	Premium Line
Instrumented Dart Impact @ 73° F		in/lb.	565
Falling Ball Impact @ 73° F	UL-746	in/lb.	900
Deflection Temperature @ 264 psi	ASTM D648	Deg. F	270
Modulus of Elasticity	ASTM D790	ksi	340
Temperature Range		Deg. F	-40 to 265
Flammable / UV Ratings	Test Spec.	Unit	Premium Line
Flame Rating - UL	UL 94	-	5VA
Outdoor UV Exposure	UL	-	F1

181610 P/N	4X IP66	6P IP68	Hinged Cover	Screw Cover	Opaque Cover	Clear Cover	Mounting Feet	Mounting Flange	Stainless Steel Locking Latch	T-Rail System
H181610S	\checkmark	\checkmark		\checkmark	\checkmark		\checkmark			\checkmark
H181610SC	\checkmark	\checkmark		\checkmark		\checkmark	\checkmark			\checkmark
H181610SF	\checkmark	\checkmark		\checkmark	\checkmark			\checkmark		\checkmark
H181610SCF	\checkmark	\checkmark		\checkmark		\checkmark		\checkmark		\checkmark
H181610H	\checkmark		\checkmark	\checkmark	\checkmark		\checkmark			\checkmark
H181610HC	\checkmark		\checkmark	\checkmark		\checkmark	\checkmark			\checkmark
H181610HF	\checkmark		\checkmark	\checkmark	\checkmark			\checkmark		\checkmark
H181610HCF	\checkmark		\checkmark	\checkmark		\checkmark		\checkmark		\checkmark
H181610HLL	\checkmark		\checkmark		\checkmark		\checkmark		\checkmark	\checkmark
H181610HCLL	\checkmark		\checkmark			\checkmark	\checkmark		\checkmark	\checkmark
H181610HFLL	\checkmark		\checkmark		\checkmark			\checkmark	\checkmark	\checkmark
H181610HCFLL	\checkmark		\checkmark			\checkmark		\checkmark	\checkmark	\checkmark
H181610H-6P	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark			\checkmark
H181610HC-6P	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark			\checkmark
H181610HF-6P	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark			\checkmark		\checkmark
H181610HCF-6P	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark		\checkmark		\checkmark

RoHS

TORQUE SPECIFICATIONS - Mounting Brackets - 1/4"-20 x 0.25 SS, countersunk phillips drive screws (torque limit = 20 in. lbs.) | Covers / Doors - Torque for corner screws is 10 in. lbs.

18X16X10 PREMIUM LINE

